Application No. 10/577,914

Response dated October 4, 2010

Reply to Office Action of September 7, 2010

## AMENDMENTS TO THE CLAIMS:

1. (Previously Presented) A process for producing metal-matrix composite materials comprising at least one portion of magnesium or of a magnesium alloy and at least one production step in which thixomolding takes place, wherein a MgsSi phase with a volumetric content of at least 2% is dispersed into the metal matrix.

(Previously Presented) The process as claimed in claim 1, wherein the metal matrix comprises magnesium or a magnesium alloy.

3. (Previously Presented) The process as claimed in claim 1, wherein a granulate of silicon or a silicon alloy and a granulate of magnesium or of a magnesium alloy are processed jointly in a thixomolding process.

4. (Previously Presented) The process as claimed in claim 3, wherein the amount and/or the size of Mg.Si phase crystallites which form and/or a silicon content of a composite material are determined via the size and/or the amount of the particles of silicon or of the silicon alloy.

2

Application No. 10/577,914

Response dated October 4, 2010

Reply to Office Action of September 7, 2010

5. (Previously Presented) The process as claimed in claim 1, wherein in the

thixomolding process the cast body is produced from the metal-matrix composite material

which is then further processed.

6. (Previously Presented) The process as claimed in claim 5, wherein the cast body is

formed from the metal-matrix composite material subsequently in at least one process step.

7. (Previously Presented) The process as claimed in claim 6, wherein the cast body is

formed from the metal-matrix composite material subsequently in at least one forging process

and/or extrusion process.

8. (Previously Presented) The process as claimed in claim 1, wherein in the production

of the composite material addition of at least roughly 2% by weight Si and at most roughly 15%

by weight Si takes place.

9. (Previously Presented) The process as claimed in claim 1, wherein a Mg2Si phase with

a volumetric content of at least roughly 5% to roughly at most roughly 40% is dispersed into a

metal matrix.

3

Application No. 10/577,914 Response dated October 4, 2010 Reply to Office Action of September 7, 2010

10. (Previously Presented) The process as claimed in claim 1, wherein in the production of metal-matrix composite material one of the standard magnesium alloys AZ91, AM50, MR1230D, MR1253M or a magnesium die casting alloy is used.

11. (Previously Presented) The process as claimed in claim 1, wherein after adding Si the heating rate of the thixomolding device is reduced when the melt first forms.

- 12. (Cancelled)
- 13. (Cancelled)
- 14. (Cancelled)